SAFETY DATA SHEET

Issuing Date 15-Feb-2011 Revision Date 19-Sep-2014 Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Fi Shock 10mile Solar Energizer (ESP10M-FS)

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Lead acid battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier NameWoodstream Corp.Supplier Address69 North Locust St.

Lititz PA 17543 US

Supplier Phone Number Phone: (717) 626-2125

Fax:(717) 626-1912

Contact Phone(717) 626-2125 mandre@woodstream.com

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

Supplier Email

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Skin corrosion/irritation	Category 1 Sub-category A



Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Harmful if swallowed

Toxic if inhaled

Causes severe skin burns and eye damage

May cause cancer

May damage fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Appearance Black Physical State Solid Odor None

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Specific treatment (see .? on this label)

Immediately call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Immediately call a POISON CENTER or doctor/physician



Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

5.5% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Lead	7439-92-1	60 - 100	*
Sulfuric acid	7664-93-9	10 - 30	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice First aid is upon rupture of sealed battery.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice. Remove contact lenses, if present and easy

to do. Continue rinsing.

Skin Contact Immediate medical attention is required. Wash off immediately with soap and

plenty of water while removing all contaminated clothes and shoes.

(U)

Inhalation

Remove to fresh air. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur. Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Lead poisoning is characterized by a metallic taste in the mouth, loss of appetite indigestion, nausea, vomiting, constipation, sleep disturbances and overall weakness. Severe exposures can lead to shock, circulatory collapse, and death.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Uniform Fire Code Corrosive: Acid-Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe

areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Should not be released into the environment. Do not allow to enter into

soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.



7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash

before reuse. Do not breathe dust. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lead	TWA: 0.05 mg/m ³	TWA: 50 μg/m³ TWA: 50 μg/m³	IDLH: 100 mg/m ³
7439-92-1		Pb	TWA: 0.050 mg/m ³
		Action Level: 30 µg/m³ Poison,	
		See 29 CFR 1910.1025 Action	
		Level: 30 µg/m3 Pb Poison, See	
		29 CFR 1910.1025	
Sulfuric acid	TWA: 0.2 mg/m³ thoracic fraction	TWA: 1 mg/m ³	IDLH: 15 mg/m ³
7664-93-9		(vacated) TWA: 1 mg/m ³	TWA: 1 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Face protection shield.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

exceeded or irritation is experienced, ventilation and evacuation may be required.



Solid

No data available

Hygiene Measures

Physical State

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. Do not breathe dust.

None known

None known

None known

None known

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Appearance Black Odor None No information available **Odor Threshold** Color No information available Property Values Remarks/ Method No data available None known pН No data available Melting / freezing point None known Boiling point / boiling range No data available None known **Flash Point** No data available None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air **Upper flammability limit** No data available Lower flammability limit No data available Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Immiscible in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known

Other Information

Kinematic viscosity

Explosive properties

Oxidizing Properties

Dynamic viscosity

Autoignition temperature

Decomposition temperature

Softening Point
VOC Content (%)
Particle Size
Particle Size Distribution
No data available
No data available



Page 7/14

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Toxic by inhalation.

Eye Contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin Contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50



Sulfuric acid	= 2140 mg/kg (Rat)	-	= 510 mg/m ³ (Rat) 2 h
7664-93-9			

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Difficulty in breathing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lead 7439-92-1	А3	Group 2A	Reasonably Anticipated	Х
Sulfuric acid 7664-93-9	A2	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.

Contains a known or suspected reproductive toxin.

Contains ingredients that have suspected developmental hazards.

Developmental Toxicity

STOT - single exposure

No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming

system and the reproductive system.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Systemic Toxicity. Reproductive

System. Blood. Central Nervous System (CNS). Gingival Tissue. Kidney. Teeth.

Cardiovascular system. Hematopoietic system. Immune system. May damage the unborn

child.



Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
628.00 mg/kg
ATEmix (inhalation-gas)
6,000.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
0.78 mg/l
ATEmix (inhalation-vapor)
15.00 ATEmix

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lead		96h LC50: = 0.44 mg/L		48h EC50: = 600 μg/L
7439-92-1		(Cyprinus carpio) 96h LC50:		
		= 1.17 mg/L (Oncorhynchus		
		mykiss) 96h LC50: = 1.32		
		mg/L (Oncorhynchus		
		mykiss)		
Sulfuric acid		96h LC50: > 500 mg/L		24h EC50: = 29 mg/L
7664-93-9		(Brachydanio rerio)		

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

(U)

Page 10/14

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D002 D008

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Lead 7439-92-1	(hazardous constituent - no waste number)	Included in waste streams: F035, F037, F038, F039, K002, K003, K005, K046, K048, K049, K051, K052, K061, K062, K064, K065, K066, K069, K086, K100, K176	= 5.0 mg/L regulatory level	

California Hazardous Waste Codes 792

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Lead	Toxic
7439-92-1	
Sulfuric acid	Toxic
7664-93-9	Corrosive

14. TRANSPORT INFORMATION

DOTNOT REGULATEDProper Shipping NameNON REGULATED

Hazard Class N/A

Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to

DOT

TDG Not regulated

Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to TDG.

MEX Not regulated

ICAO Not regulated

IATA Not regulated
Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to

IMDG/IMO

RID Not regulated

ADR Not regulated



ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lead - 7439-92-1	7439-92-1	60 - 100	0.1
Sulfuric acid - 7664-93-9	7664-93-9	10 - 30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Lead 7439-92-1		X	X	
Sulfuric acid 7664-93-9	1000 lb			Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Lead 7439-92-1	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Sulfuric acid 7664-93-9	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Lead - 7439-92-1	Carcinogen Developmental
	Female Reproductive
	Male Reproductive
Sulfuric acid - 7664-93-9	Carcinogen



U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lead 7439-92-1	Х	X	X	X	X
Sulfuric acid 7664-93-9	Х	Х	X	Х	Х
Tin 7440-31-5	Х	Х	X		
Calcium 7440-70-2	X	Х	Х		

International Regulations

Mexico

National occupational exposure limits

Matienal ecoapational expectate innite		
Component	Carcinogen Status	Exposure Limits
Lead 7439-92-1 (60 - 100)	A3	Mexico: TWA= 0.15 mg/m ³
Sulfuric acid 7664-93-9 (10 - 30)	A2	Mexico: TWA 1 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

Canada WHMIS Hazard Class

Non-controlled



16 OTHER INFORMATION	ını

NFPA Health Hazards 0 Flammability 0 Instability 0 Physical and Chemical Hazards HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date15-Feb-2011Revision Date19-Sep-2014

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text



End of Safety Data Sheet

